



## SPECIALTY

# BOLT® Quick Dry

## Siliconized Acrylic Latex Caulk



White Lightning® BOLT® Quick Dry is a durable caulk that makes quick work of interior and exterior caulking projects. This Quick Dry formula can be painted within 30 minutes, keeping even the most time sensitive projects on track. Ideal for filling joints and openings around doors, windows, baseboards, trim, siding and vents. For use on: wood, drywall, metal, glass and masonry.

- Paintable in 30 Minutes
- Flexible and Crack Resistant
- Cured Sealant is Mold & Mildew Resistant



PAINTABLE



INTERIOR/  
EXTERIOR



WATER  
CLEANUP

PART #	UPC	Color	SIZE
W31010010	0-23275-20510-9	White	10 fl oz
W31010005	0-23275-20501-7	White	5.5 fl oz



  
**WHITE  
LIGHTNING®****SPECIALTY  
BOLT® Quick Dry**

### Product Description:

White Lightning® BOLT® Quick Dry is a durable caulk that makes quick work of interior and exterior caulking projects. This Quick Dry formula can be painted within 30 minutes, keeping even the most time sensitive projects on track. Ideal for filling joints and openings around doors, windows, baseboards, trim, siding and vents. For use on: wood, drywall, metal, glass and masonry.

### Physical Properties:

**Type:** Styrene Acrylic

**Colors:** White

**Shelf Life:** 24 Months

**Flash Point:** N/A (water based)

**Flammability:** N/A (water based)

**Full Cure Time:** 5-7 Days

**Tack Free Time:** 10 Minutes

**Application Temperature:** 40° F to 140° F

**Service Temperature:** -30° F to 180° F

**Vehicle:** Styrene Acrylic

**Solids by Weight:** 76.3%

**Weight/Gallon:** 12.6 lbs/gal

**Paintable:** Paintable

**Primers:** Not required

**Mildew Resistance:** Good

**Water resistance:** Good

**Odor:** Low

**Shrinkage:** Low

### Performance Data:

**Joint Size:** 1/8" x 1/8" to 1/2" x 1/2"

**Freeze-Thaw Stability:** Passes Through 5 Cycles

**Shelf Life:** 24 Months

**Clean Up:** Water; promptly clean tools and excess caulk with water or a damp cloth.

**Flexibility:** Good

**Linear Coverage:** 10oz cartridge 24ft at 1/4" wide by 1/4" deep bead; 5.5oz squeeze tube 12ft at 1/4" wide by 1/4" deep bead.

**Paintable:** Can be painted after 30 minutes at 75°F and 50% relative humidity. Allow extra dry time during periods of high humidity and/or cool temperatures.

**ASTM:** Meets performance requirements of ASTM C-920, Class 12.5

### Application:

- 1.Remove all existing caulk
- 2.Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
- 3.Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

#### 10oz cartridge

- Cut cartridge tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

#### 5.5oz squeeze tube

- Remove cap, cut tube tip 45° angle.
- Squeeze tube to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

### Clean Up:

Water; promptly clean tools and excess caulk with water or a damp cloth.

### Cautions:

See SDS

### LIMITED WARRANTY:

LIMITED WARRANTY: For 40 years from date of purchase, if when applied according to label directions within one year from date of purchase, if this product fails to perform in accordance with the specifications set forth on this label, as your sole remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. Applies to single family house only. This warranty is made to the original residential consumer purchaser and is not transferable. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

**For more information please call or write:**

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)