

# **Safety Data Sheet**

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 09-6403-1
 Version Number:
 8.00

 Issue Date:
 05/21/18
 Supercedes Date:
 04/16/15

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M(TM) Hot Melt Adhesive 3748-Q, 3748-B, Black

#### **Product Identification Numbers**

62-3724-9132-4, 62-3724-9335-3

#### 1.2. Recommended use and restrictions on use

### Recommended use

Adhesive

### 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Industrial Adhesives and Tapes Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

## 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

#### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### 2.2. Label elements

## Signal word

Not applicable.

## Symbols

Not applicable.

### **Pictograms**

Not applicable.

## **SECTION 3: Composition/information on ingredients**

Page 1 of 9

Ingredient	C.A.S. No.	% by Wt
Polypropylene	9003-07-0	10 - 40 Trade Secret *
Hydrocarbon Resin - N.J.T.S. Reg. No. 04499600-7079	Trade Secret*	20 - 30 Trade Secret *
Ethylene-Propylene Polymer	9010-79-1	1 - 25 Trade Secret *
Polyethylene	9002-88-4	1 - 20 Trade Secret *
Styrene-Butadiene Polymer - N.J.T.S. Reg. No. 04499600-7080	Trade Secret*	1 - 20 Trade Secret *
Polyolefin Wax	8002-74-2	1 - 15 Trade Secret *
Stabilizer	6683-19-8	0.1 - 5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation:

No need for first aid is anticipated.

### **Skin Contact:**

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

### **Eye Contact:**

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

#### If Swallowed:

No need for first aid is anticipated.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

## 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

Substance
Hydrocarbons
Carbon monoxide
Carbon dioxide

# Condition

During Combustion During Combustion During Combustion

#### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin contact with hot material. For industrial or professional use only.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Polyolefin Wax	8002-74-2	ACGIH	TWA(as fume):2 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

No engineering controls required.

### 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

**Indirect Vented Goggles** 

#### Skin/hand protection

No chemical protective gloves are required.

#### **Respiratory protection**

None required.

#### Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

General Physical Form: Solid
Specific Physical Form: Waxy Solid

Odor, Color, Grade:black, mild resinous odor.Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNot ApplicableBoiling PointNot Applicable

Flash Point 280 °C [Test Method: Cleveland Open Cup]

Evaporation rateNot ApplicableFlammability (solid, gas)Not ClassifiedFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

Vapor PressureNilVapor DensityNilDensity0.92 g/cm3

Specific Gravity 0.92 [Ref Std:WATER=1]

Solubility in Water Nil

**Solubility- non-water**Partition coefficient: n-octanol/ water
No Data Available
No Data Available

**Autoignition temperature** 330 °C

**Decomposition temperature**No Data Available**Viscosity**No Data Available

Hazardous Air Pollutants 0 % weight [Test Method: Calculated]

**Volatile Organic Compounds** 0 g/l [*Test Method:*calculated SCAQMD rule 443.1]

**Percent volatile** 0 % weight

VOC Less H2O & Exempt Solvents 0 g/l [Test Method:calculated SCAQMD rule 443.1]

Solids Content 100 %

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

## 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

Page 4 of

#### 10.5. Incompatible materials

None known.

## 10.6. Hazardous decomposition products

**Substance** 

None known.

**Condition** 

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

No health effects are expected.

#### **Skin Contact:**

During heating:

Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

# **Eye Contact:**

During heating:

Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

### **Ingestion:**

No known health effects.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polypropylene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polypropylene	Ingestion	Mouse	LD50 > 8,000 mg/kg
Hydrocarbon Resin - N.J.T.S. Reg. No. 04499600-7079	Dermal	Rat	LD50 > 2,000 mg/kg
Hydrocarbon Resin - N.J.T.S. Reg. No. 04499600-7079	Ingestion	Rat	LD50 > 5,000  mg/kg
Ethylene-Propylene Polymer	Dermal	Rabbit	LD50 > 2,000 mg/kg
Ethylene-Propylene Polymer	Ingestion	Rat	LD50 > 5,000  mg/kg
Styrene-Butadiene Polymer - N.J.T.S. Reg. No. 04499600-7080	Dermal		LD50 estimated to be > 5,000 mg/kg
Styrene-Butadiene Polymer - N.J.T.S. Reg. No. 04499600-7080	Ingestion		LD50 estimated to be > 5,000 mg/kg
Polyethylene	Dermal		LD50 estimated to be > 5,000 mg/kg

Page 5 of 9

## 3M(TM) Hot Melt Adhesive 3748-Q, 3748-B, Black

05/21/18

Polyethylene	Ingestion	Rat	LD50 > 2,000 mg/kg
Polyolefin Wax	Dermal	Rat	LD50 > 5,000 mg/kg
Polyolefin Wax	Ingestion	Rat	LD50 > 5,000 mg/kg
Stabilizer	Dermal	Rabbit	LD50 > 3,160 mg/kg
Stabilizer	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.95 mg/l
Stabilizer	(4 nours) Ingestion	Rat	LD50 > 10,250 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
Polypropylene	Human	No significant irritation
	and	
	animal	
Ethylene-Propylene Polymer	Rabbit	No significant irritation
Polyethylene	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Polyolefin Wax	Rabbit	No significant irritation
Stabilizer	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Polypropylene	Professio	No significant irritation
Тотургоручене	nal	No significant irritation
	judgeme	
	nt	
Ethylene-Propylene Polymer	Rabbit	No significant irritation
Polyolefin Wax	Rabbit	No significant irritation
Stabilizer	Rabbit	Mild irritant

## **Skin Sensitization**

Name	Species	Value
Polypropylene	Human	Not classified
	and	
	animal	
Polyolefin Wax	Guinea	Not classified
	pig	
Stabilizer	Human	Not classified
	and	
	animal	

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Polyolefin Wax	In Vitro	Not mutagenic
Stabilizer	In Vitro	Not mutagenic
Stabilizer	In vivo	Not mutagenic

Carcinogenicity

Caremogenicity			
Name	Route	Species	Value
Polypropylene	Not	Rat	Some positive data exist, but the data are not
	Specified		sufficient for classification
Polyethylene	Not	Multiple	Some positive data exist, but the data are not
	Specified	animal	sufficient for classification

3M(TM) Hot Melt Adhesive 3748-Q, 3748-B, Black	05/21/18
--	----------

		species	
Polyolefin Wax	Ingestion	Rat	Not carcinogenic
Stabilizer	Ingestion	Multiple	Not carcinogenic
		animal	_
		species	

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Stabilizer	Ingestion	Not classified for female reproduction	Rat	NOAEL 688 mg/kg/day	2 generation
Stabilizer	Ingestion	Not classified for male reproduction	Rat	NOAEL 688 mg/kg/day	2 generation
Stabilizer	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,000 mg/kg/day	during organogenesi s

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Polyolefin Wax	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	90 days
Polyolefin Wax	Ingestion	hematopoietic system   liver   immune system   skin   endocrine system   bone, teeth, nails, and/or hair   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Stabilizer	Ingestion	endocrine system	Not classified	Rat	NOAEL 450 mg/kg/day	2 years
Stabilizer	Ingestion	liver	Not classified	Dog	NOAEL 302 mg/kg/day	90 days
Stabilizer	Ingestion	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Stabilizer	Ingestion	auditory system   eyes	Not classified	Dog	NOAEL 302 mg/kg/day	90 days

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

## **Ecotoxicological information**

Page 7 of 9

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

# **SECTION 15: Regulatory information**

### 15.1. US Federal Regulations

Contact 3M for more information.

#### **EPCRA 311/312 Hazard Classifications:**

## Physical Hazards

Not applicable

#### **Health Hazards**

Not applicable

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

Page 8 of

05/21/18

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

NFPA Hazard Classification

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 09-6403-1
 Version Number:
 8.00

 Issue Date:
 05/21/18
 Supercedes Date:
 04/16/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 9 of 9